

**Data sheet**  
**MP 132-1500**

Swivel castor - mounting type: top plate (4 bolt holes).



**Specifications**

|                           |                                                                                       |                  |
|---------------------------|---------------------------------------------------------------------------------------|------------------|
| Diameter (D)              |    | 96 mm            |
| Wheel width (S)           |   | 56 mm            |
| Plate size (A x B)        |  | 100 x 100 mm     |
| Bolt hole spacing (a x b) |  | 70 x 70 mm       |
| Load                      |  | 1500 kg          |
| Mounting type             |                                                                                       | Mounting bracket |
| Wheel centre colour       |                                                                                       | Black            |
| Wheel centre              |                                                                                       | Polyamide        |
| Bolt holes Ø              |  | 13 mm            |
| Mounting height(H)        |  | 132 mm           |
| Tread material            |                                                                                       | Plastic          |
| Farba behúňa              |                                                                                       | Čierna           |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).