


Data sheet

623T ALU-G180

Swivel castor - mounting type: top plate (4 bolt holes).



Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Discription of the brake T:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALU series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- non-marking
- yellow-brown color

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness $\geq 90^\circ$ Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness $< 90^\circ$ Shore; temperature 17°C - 23°C ; humidity = 40%-70%).

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	
ROLLING RESISTANCE	very good	
OPERATING NOISE	good	
WEAR RESISTANCE	excellent	
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		180 mm
Wheel width (S)		50 mm
Plate size (A x B)		135 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		56 mm
Mounting height(H)		230 mm
Load		350 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Polyuretán
Attributes		Non-marking
Farba behúňa		Žltá-Hnedá
Wheel centre colour		Hliníková
Wheel centre		Hliníková liatina
Typ brzd		T