


# Data sheet

## 673 ALU-G100 H1

Swivel castor - mounting type: plug-in solid stem.



### Bracket 673 series:

#### Swivel castor with plug-in solid stem

- standard version
- steel THK 3 ÷ 3,5 mm
- double ball bearing with calibrated races
- zinc-plated, Cr6-free

### Wheel ALU series:

#### Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

#### Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- non-marking
- yellow-brown color

#### Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

### Bearing - ball:

- two radial ball bearing with sealing covers

|                         |                     |  |
|-------------------------|---------------------|--|
| TREAD AND TYRE HARDNESS | 92° ± 3° Shore A    |  |
| ROLLING RESISTANCE      | very good           |  |
| OPERATING NOISE         | good                |  |
| WEAR RESISTANCE         | excellent           |  |
| TEMPERATURE RANGE       | od -20 °C do +70 °C |  |

### Specifications

|                           |  |                   |
|---------------------------|--|-------------------|
| Diameter (D)              |  | 100 mm            |
| Wheel width (S)           |  | 40 mm             |
| Priemer príruby vidlice   |  | 102 mm            |
| Priemer upínacieho drieku |  | 27 mm             |
| Dĺžka upínacieho drieku   |  | 65 mm             |
| Offset (F)                |  | 56 mm             |
| Mounting height(H)        |  | 135 mm            |
| Load                      |  | 220 kg            |
| Bearing type              |  | Ball              |
| Mounting type             |  | Hladký driek      |
| Tread material            |  | Polyuretán        |
| Attributes                |  | Non-marking       |
| Farba behúňa              |  | Žltá-Hnedá        |
| Wheel centre colour       |  | Hliníková         |
| Wheel centre              |  | Hliníková liatina |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).