


Data sheet

433 VD-CPS-G100-26









Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

| | | |
|-------------------------|-----------------------|--|
| TREAD AND TYRE HARDNESS | 98° ± 2° Shore A | <div><div></div><div></div><div></div><div></div><div></div></div> |
| ROLLING RESISTANCE | very good | <div><div></div><div></div><div></div><div></div><div></div></div> |
| OPERATING NOISE | good | <div><div></div><div></div><div></div><div></div><div></div></div> |
| WEAR RESISTANCE | very good | <div><div></div><div></div><div></div><div></div><div></div></div> |
| TEMPERATURE RANGE | from -20 °C to +60 °C | |

Specifications

| | | |
|---------------------------|---|------------------|
| Diameter (D) |  | 100 mm |
| Wheel width (S) |  | 26 mm |
| Plate size (A x B) |  | 105 x 85 mm |
| Bolt hole spacing (a x b) |  | 80 x 60 mm |
| Bolt holes Ø |  | 9 mm |
| Mounting height(H) |  | 75 mm |
| Load |  | 128 kg |
| Bearing type |  | Ball |
| Mounting type | | Mounting bracket |
| Tread material | | Plastic |
| Attributes | | Non-marking |
| Wheel centre colour | | Prírodná biela |
| Wheel centre | | Polyamide |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).