


Data sheet

632 CNC-K125

Fixed castor - mounting type: top plate (4 bolt holes).



Bracket 632 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Wheel CNC series:

Polypropylene:

- corrosion-free
- high chemical resistance to a wide variety of aggressive substances (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- devices and machines with min. manipulation

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	
ROLLING RESISTANCE	very good	
OPERATING NOISE	good	
WEAR RESISTANCE	very good	
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		125 mm
Wheel width (S)		40 mm
Plate size (A x B)		140 x 110 mm
Bolt hole spacing (a x b)		105 x 80/75 mm
Bolt holes Ø		11 mm
Mounting height(H)		162 mm
Load		150 kg
Bearing type		Klzné
Mounting type		Mounting bracket
Tread material		Plastic
Attributes		Non-marking
Wheel centre colour		Prírodná biela
Wheel centre		Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).