

Data sheet

734 CPC-G125-45

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Vidlica série 734:

Pevné rolovacie koliesko s montážnou doskou na štyri otvory

- tvarovo zosilnený oceľový plech so zvýšenou pevnosťou
- zinkované bez Cr6

Wheel CPC series:

Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concentrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	70° Shore D	● ● ● ● ● ● ● ●
ROLLING RESISTANCE	excellent	● ● ● ● ● ● ● ●
OPERATING NOISE	satisfactory	● ● ● ● ● ● ● ●
WEAR RESISTANCE	good	● ● ● ● ● ● ● ●
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Priemer (D)	 125 mm
Šírka kolesa (S)	 45 mm
Rozmer montážnej dosky (A x B)	 135 x 110 mm
Rozteč upínacích otvorov (a x b)	 105 x 80/75 mm
Priemer upínacích otvorov	 11 mm
Celková výška (H)	 170 mm
Nosnosť	 300 kg
Typ ložiska	 Ball
Upevnenie	Montážna doska na 4 otvory
Behúň	Plast
Vlastnosti	Bezstopé
Farba disku	Prírodná biela
Materiál disku	Polyamid

Pri výbere vhodného kolesa sa prosím zoznámte s technickými podmienkami a spôsobom výberu kolies, ktorý je uvedený v našom katalógu RENOST alebo na www.renost.sk

Poznámka: Uvádzaná nosnosť rolovacieho kolieska, kolesa platí pri dynamickom zaťažení podľa STN EN 12532 (rýchlosť 4 km/hod.; výška prekážky pre kolesá - s tvrdosťou behúňa $\geq 90^\circ$ Shore: 2,5% z priemeru kolesa, s tvrdosťou behúňa $< 90^\circ$ Shore: 5,0% z priemeru kolesa; teplota od 17°C do 23°C; vlhkosť vzduchu od 40% do 70%).