

Data sheet

453 ALU-G075-25

Swivel castor - mounting type: bolt hole.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Bracket 453 series:

Swivel castor with bolt hole

- pressed steel THK 3 ÷ 3,5 mm
- double ball bearing with calibrated races
- zinc-plated, Cr6-free

Wheel ALU series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- non-marking
- yellow-brown color

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	
ROLLING RESISTANCE	very good	
OPERATING NOISE	good	
WEAR RESISTANCE	excellent	
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		75 mm
Wheel width (S)		25 mm
Priemer príruby vidlice		76 mm
Bolt hole Ø		12.5 mm
Offset (F)		40 mm
Mounting height(H)		97 mm
Load		130 kg
Bearing type		Ball
Mounting type		Stredový otvor
Tread material		Polyuretán
Attributes		Non-marking
Farba behúňa		Žlto-Hnedá
Wheel centre colour		Hliníková
Wheel centre		Hliníková liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).