

Data sheet

623 LU-G100

Swivel castor - mounting type: top plate (4 bolt holes).



Bracket 623 series:

Swivel castor with top plate (4 bolt holes)

- standard version
- pressed steel, THK 3 ÷ 4 mm
- double bearing with calibrated races
- seal in the swivel head
- zinc-plated, Cr6-free

Wheel LU series:

Wheel center:

- one-piece
- grey cast iron (STN 42 2420)
- reinforced supporting rib
- anti-corrosion paint
- grey color

Tread:

- casted polyurethane elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and good at preserving floor surfaces
- non-marking
- low level of starting and rolling resistance
- brown color

Application:

- flat concrete floors
- small obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	
ROLLING RESISTANCE	very good	
OPERATING NOISE	good	
WEAR RESISTANCE	very good	
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		100 mm
Wheel width (S)		50 mm
Bearing type		Ball
Plate size (A x B)		135x110 mm
Bolt hole spacing (a x b)		105x80/75 mm
Bolt holes Ø		11 mm
Offset (F)		56 mm
Mounting height(H)		140 mm
Load		350 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).