


Data sheet

624 ALU-G100

Swivel castor - mounting type: top plate (4 bolt holes).



Bracket 624 series:

Swivel castor with top plate (4 bolt holes)

- medium-duty version
- pressed steel, THK 4 ÷ 5 mm
- double ball bearing with calibrated races
- swivel head seal
- zinc-plated, Cr6-free

Wheel ALU series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- non-marking
- yellow-brown color

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	
ROLLING RESISTANCE	very good	
OPERATING NOISE	good	
WEAR RESISTANCE	excellent	
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)	100 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	60 mm
Mounting height(H)	140 mm
Load	220 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Žltá-Hnedá
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).