

Data sheet

CPC-K200/22

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Wheel CPC series: Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concentrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	70° Shore D	
ROLLING RESISTANCE	excellent	
OPERATING NOISE	satisfactory	
WEAR RESISTANCE	good	
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)		200 mm
Wheel width (S)		50 mm
Dĺžka náboja (L)		60 mm
Vnútorný priemer náboja (d)		22 mm
Bearing type		Klzné
Load		800 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website <https://sk.renost.net/en/>. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness $\geq 90^\circ$ Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness $< 90^\circ$ Shore; temperature 17°C-23°C; humidity= 40%-70%).