Data sheet
632 NMB-K200

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 632 is fixed rolovacie castor with mounting doskou na four otvory, which uses zinc-plated vidlicu z steel plechu without Cr6 for zvýšenú durability. The design includes polypropylénový wheel centre durable to prasknutiu vo svetlo-sivej farbe and thermoplastic gumový elastomérový tread v tmavo-sivej farbe, mechanicky non-detachably combined with wheel centre, which ensures reliability and quiet non-marking operation. Thanks to kĺznému bearing tvorenému material wheel centre is toto castor bezúdržbové, odolné to dirt, external vplyvom and zmenám prostredia, which ho robí vhodným for various industrial and komerčné applications. An ideal choice for lightweight manipulačné equipment, where vyžaduje efektívna and tichá manipulácia na krátkych prepravných vzdialenostiach.

Bracket 632 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Wheel NMB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment

Bearing - plain bore:

- formed by wheel center material
- maintenance-free

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	140 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	240 mm
Load	200 kg
Bearing type	Kĺzné
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).