Data sheet
423F PYR-V125

Swivel castor - mounting type: top plate (4 bolt holes).



The series model 423 PYR predstavuje swivel rolovacie castor with integrovanou brake, which is určené for montáž using prírubovej dosky na four otvory. Thanks to the use of high-quality tread z thermoplastic elastomer and durable wheel centre achieves non-marking operation with minimálnym hlukom. Zinc-plated vidlica v kombinácii with klzným bearing ensures maintenance-free operation and long service life aj during intenzívnom zaťažení. An ideal choice for industrial and skladové prostredia, where important reliability and gentleness k povrchom.

TREAD AND TYRE HARDNESS	75° ± 2° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).