Data sheet
634 PUC-K200 SS

Fixed castor - mounting type: top plate (4 bolt holes).



Thanks to the use of high-quality material and pokročilého technického solution toto castor offers vynikajúce operating vlastnosti. Tread z thermoplastic elastomer is pevne combined with wheel centre, thereby guarantees a long service life and stability during zaťažení. Klzné bearing ensures maintenance-free operation and smooth movement, while the zinc-plated vidlica increases resistance to corrosion. An ideal choice for applications v industrial and komerčných priestoroch, where important reliability and quiet operation.

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).