Data sheet
724F ALE-G160

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors with brake uses vidlicu series 724 vyrobenú z steel plechu thickness 4 až 6 mm, which is zinc-plated without Cr6 for antikoróznu protection. Wheel centre z hliníkovej liatiny with uzatvoreným rebrovaním increases strength, while the plný elastický rubber tread, navulkanizovaný na wheel centre, ensures veľmi dobrú priechodnosť cez nerovnosti and quiet operation. Mechanizmus brake F blocks rotation wheel and vidlice v current direction, thereby increases safety. Thanks to dvom radiálnym ball ložiskám with krytmi and kovanému nosnému dielu bearing achieves high load capacity and durability. An ideal choice for tvrdé pancierové floor and suitable aj na nerovné surfaces, where provides výborné tlmenie vibrácií and maintenance-free operation.

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALE series:

Wheel center:

- aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- elastic solid rubber
- chemically-bonded inseparable connection with the wheel center (vulkanized)
- excellent at crossing obstacles
- vibration-absorbing
- silent operation
- black color

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)	160 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 × 110 mm
Bolt hole spacing (a x b)	105 × 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	205 mm
Load	350 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Nízka hlučnosť
Farba behúňa	Čierna
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).