Data sheet
633X NMB-K160

Nerezové pevné rolovacie koliesko - spôsob upnutia: montážna doska na štyri otvory (príruba).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

INOX
NEHRDZAVEJÚCA OCEĽ

Vidlica series 633X provides fixed rolovacie castor with mounting doskou na four otvory vyrobenou z nerezového plechu. Wheel centre z polypropylene is durable to prasknutiu and má svetlo-sivú farbu, zatiaľčo tread z thermoplastic rubber elastomer is non-detachably mechanicky combined with wheel centre and disponuje tmavo-sivou farbou. Thanks to the use of klzného bearing tvoreného material wheel centre ensures maintenance-free operation, which is durable to dirt, external vplyvom and zmenám prostredia. An ideal choice for lightweight manipulačné equipment and short transport distances.

Bracket 633X series:

Fixed castor with top plate (4 bolt holes)

- stainless steel

Wheel NMB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	85° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	160 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	195 mm
Load	200 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).