Data sheet
433 CZC-K125

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 433 CZC is fixed rolovacie castor with mounting doskou na four otvory, ideálne for use v lakovniach with teplotou pece krátkodobo do +240°C. The design uses vstrekovaný teplotne durable polyamide wheel centre, which is durable to vysokým temperatures and prasknutiu, with prírodnou bielou farbou. Thanks to klznému bearing, tvorenému material wheel centre, ensures maintenance-free operation and resistance to dirt, external vplyvom and zmenám prostredia. An ideal choice for short transport distances, while teplota wheel nesmie prekročiť +150°C, which platí len during použití montážneho kompletu with teflónovým povrchom. Toto wheel offers reliable and odolnú konštrukciu for demanding industrial applications.

Bracket 433 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Wheel CZC series:

Injection heat-resistant polyamide:

- abrasion resistant
- natural white color

Application:

- paint shops
- oven temperature short-term up to +240°C
- wheel temperature must not exceed +150 °C

*temperature resistance only applies when using a teflon tube

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +150 °C	

Specifications

Diameter (D)	125 mm
Plate size (A x B)	105 x 85 mm
Bolt hole spacing (a x b)	80 x 60 mm
Bolt holes Ø	9 mm
Mounting height(H)	155 mm
Load	200 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Krémová
Wheel centre	Polyamide
Wheel width (S)	35 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).