Data sheet
222B CPA-K075

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors combines zinc-plated vidlicu z steel plechu with mounting doskou na four otvory, which allows simple and bezpečnú installation. Vstrekovaný polyamide wheel centre vykazuje výnimočnú resistance to corrosion and chemicals, including alkoholu, solí, tukov and zriedených kyselín či zásad. Klzné bearing, tvorené material wheel centre, ensures maintenance-free operation with high durability to dirt and external vplyvom, which is ideálne for prostredia with minimálnou manipuláciou. Mechanizmus brake typu B locks rotation wheel, poskytujúc dodatočnú safety during stabilizácii equipment. Thanks to týmto vlastnostiam is toto castor optimálnou voľbou for prístroje and stroje na short transport distances, where vyžaduje reliability and nízká maintenance.

Bracket 222 series:

Swivel castor with top plate (4 bolt holes)

- pressed steel, THK 2 mm
- double-row axial bearing in the swivel head
- zinc-plated, Cr6-free

Discription of the brake B:

- the brake system prevents the rotation of the wheel

Wheel CPA series:
Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concenrations (see spreadsheet chemical resistance of materials)

Application:

- devices and machines with min. manipulation

Bearing - plain bore:

- formed by wheel center material
- maintenance-free
- resistant to dirt and external influences and environmental changes
- suitable for short distances

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	75 mm
Wheel width (S)	22 mm
Plate size (A x B)	60 × 60 mm
Bolt hole spacing (a x b)	47/40 × 47/40 mm
Bolt holes Ø	6,3 mm
Offset (F)	24 mm
Mounting height(H)	99 mm
Load	50 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Polyamide
Typ brzdy	B

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).