Data sheet
323F NOB-V080

Swivel castor - mounting type: top plate (4 bolt holes).



Thanks to the use of thermoplastic elastomer v behúni ensures toto castor non-marking operation and protection floors pred poškodením. Zinc-plated vidlica with kvalitným bearing guarantees hladkú rotáciu and long service life aj during intenzívnej operation. An ideal choice for industrial and komerčné prostredia, where potrebná spoľahlivá brake and jednoduchá montáž cez prírubovú dosku.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		80 mm
Wheel width (S)		30 mm
Bearing type		Ihlové
Plate size (A x B)		95x70 mm
Bolt hole spacing (a x b)		75/72x52/45 mm
Bolt holes Ø		9 mm
Offset (F)		38 mm
Mounting height(H)		160 mm
Load		100 kg
Tread material		Guma a TPE
Farba behúňa		Sivá
Wheel centre		Polypropylén
Wheel centre colour		Sivá

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).