Data sheet
323 NOB-V125

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this castor uses thermoplastic elastomér for tread, which provides tichú operation and high durability against wear. Thanks to the use of guličkového bearing achieves plynulý and maintenance-free movement, ideálny for industrial and komerčné prostredia. Mounting doska na four otvory allows simple and bezpečnú installation, zvyšujúc stability during zaťažení. An ideal choice for applications vyžadujúce reliability and gentleness k povrchom.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		125 mm
Wheel width (S)		32 mm
Bearing type		Ihlové
Plate size (A x B)		95x70 mm
Bolt hole spacing (a x b)		75/72x52/45 mm
Bolt holes Ø		9 mm
Offset (F)		38 mm
Mounting height(H)		160 mm
Load		100 kg
Tread material		Guma a TPE
Farba behúňa		Sivá
Wheel centre		Polypropylén
Wheel centre colour		Sivá

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).