Data sheet
323 NOB-K080

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this castor includes wheel centre z durable material combined with behúňom z thermoplastic elastomer, which provides excellent trakciu and saves surfaces. Thanks to the use of high-quality bearing, such as is ihličkové alebo ball, ensures plynulú and maintenance-free operation. An ideal choice for industrial and komerčné prostredia, where important reliability and long service life.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		80 mm
Wheel width (S)		30 mm
Bearing type		Klzné
Plate size (A x B)		95x70 mm
Bolt hole spacing (a x b)		75/72x52/45 mm
Bolt holes Ø		9 mm
Offset (F)		38 mm
Mounting height(H)		116 mm
Load		90 kg
Tread material		Guma a TPE
Farba behúňa		Sivá
Wheel centre		Polypropylén
Wheel centre colour		Sivá

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).