Data sheet
303 NOB-V075

Fixed castor - mounting type: bolt hole.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this rolovacieho castors includes vidlicu series 303 vyrobenú z pozinkovaného steel plechu without Cr6, which ensures durability against corrosion and long service life. Wheel centre z polypropylene is durable to prasknutiu and is svetlo-sivej farby, while the tread z thermoplastic rubber elastomer v tmavo-sivej farbe is mechanicky combined with wheel centre, which guarantees quiet and non-marking operation without the need for maintenance. Use ihlového bearing, where vonkajší krúžok tvorí material wheel centre with ihlíčkami z steel and klietkou z polyamidu PA6, allows smooth movement and is suitable for short transport distances. An ideal choice for applications v skladoch, small výrobách and prevádzkach, where important reliability and gentleness k podlahe.

Bracket 303 series:

Swivel castor with bolt hole

- pressed steel
- zinc-plated, Cr6-free

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - roller:

- the outer ring of the bearing formed by the wheel center material

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		75 mm
Wheel width (S)		30 mm
Priemer príruby vidlice		60 mm
Bolt hole Ø		10.2 mm
Mounting height(H)		100 mm
Load		100 kg
Bearing type		Ihlové
Mounting type		Stredový otvor
Tread material		Guma a TPE
Attributes		Non-marking
Farba behúňa		Sivá
Wheel centre colour		Sivá
Wheel centre		Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).