Data sheet
383 NOB-V100

Fixed castor - mounting type: top plate (4 bolt holes).



Thanks to the use of thermoplastic elastomer v behúni toto castor provides gentle kontakt with surfaces and redukuje hlučnosť during pohybe. Klzné bearing ensures maintenance-free operation and long service life, while the zinc-plated vidlica increases resistance to corrosion. An ideal choice for industrial and komerčné prostredia, where important reliability and ochrana floor krytín.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	100 mm
Wheel width (S)	32 mm
Bearing type	Ihlové
Plate size (A x B)	95x70 mm
Bolt hole spacing (a x b)	75/72x52/45 mm
Bolt holes Ø	9 mm
Mounting height(H)	135 mm
Load	100 kg
Tread material	Guma a TPE
Farba behúňa	Sivá
Wheel centre	Polypropylén
Wheel centre colour	Sivá

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).