Data sheet
353 NOB-K125

Swivel castor - mounting type: bolt hole.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors includes vidlicu z pozinkovaného steel plechu thickness 2,5 mm with dvojradovým axial bearing, which ensures hladkú otočnosť and resistance to dirt and external vplyvom. Wheel centre z polypropylene is durable to prasknutiu and v svetlo-sivej farbe, while tread z thermoplastic rubber elastomer v tmavo-sivej farbe is mechanicky combined with wheel centre, which guarantees quiet and non-marking operation. Thanks to klznému bearing is castor bezúdržbové and suitable na short transport distances, which ho robí ideálnou voľbou for lightweight manipulačné equipment v skladoch, small výrobách and prevádzkach, where vyžaduje reliability and gentleness k podlahe.

Bracket 353 series:

Swivel castor with bolt hole

- pressed steel, THK 2,5 mm
- double-row axial bearing in the swivel head
- zinc-plated, Cr6-free

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - plain bore:

- formed by wheel center material

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	125 mm
Wheel width (S)	32 mm
Priemer príruby vidlice	60 mm
Bolt hole Ø	11 mm
Offset (F)	40 mm
Mounting height(H)	160 mm
Load	100 kg
Bearing type	Klzné
Mounting type	Stredový otvor
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).