Data sheet
353 NOB-g100 p

Swivel castor - mounting type: bolt hole.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 353 NOB-g predstavuje swivel rolovacie castor with montážnym hole na skrutku, where konštrukčné riešenie uses steel plech thickness 2,5 mm for vidlicu, which is zinc-plated without Cr6 for zvýšenú durability. Wheel centre is made z polypropylene, which guarantees durability against prasknutiu and svetlo-sivú farbu, while the tread z thermoplastic rubber elastomer is mechanicky combined with wheel centre, thereby ensures quiet and non-marking operation v tmavo-sivej farbe. Thanks to dvojradovému axial bearing v smerovej otoči and jedno radiálnemu ball bearing with cover v hub wheel, zakrytému thread guard cover, toto castor offers high reliability and maintenance-free operation. An ideal choice for lightweight manipulačné equipment suitable do skladov, small výrob and operations, where important gentleness k podlahe and efektívna manipulácia.

Bracket 353 series:

Swivel castor with bolt hole

- pressed steel, THK 2,5 mm
- double-row axial bearing in the swivel head
- zinc-plated, Cr6-free

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	100 mm
Wheel width (S)	32 mm
Priemer príruby vidlice	60 mm
Bolt hole Ø	11 mm
Offset (F)	38 mm
Mounting height(H)	135 mm
Load	100 kg
Bearing type	Ball
Mounting type	Stredový otvor
Tread material	Guma a TPE
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

Bearing - ball:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).