Data sheet
353F NOB-V125

Swivel castor - mounting type: bolt hole, with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors z radu 353 NOB-V uses mounting hole na skrutku na simple installation. Vidlica is made z steel plechu thickness 2,5 mm and zinc-plated without Cr6, which increases durability against corrosion. Dvojradové axial ihlové bearing ensures plynulú otočnosť with low údržbou, while vonkajší krúžok bearing is integrálnou súčasťou polypropylene wheel centre, which is durable to prasknutiu and má svetlo-sivú farbu. Tread z thermoplastic rubber elastomer is mechanicky combined with wheel centre, poskytujúc quiet and non-marking operation v tmavo-sivej farbe, thereby saves podlahové surfaces. Mechanizmus brake typu F blocks rotation wheel and vidlice v current direction, zvyšujúc safety during handling. Thanks to týmto vlastnostiam is toto castor suitable for short transport distances v environments such as sklady, malé výroby and operation, where important reliability and jednoduchá obsluha.

Bracket 353 series:

Swivel castor with bolt hole

- pressed steel, THK 2,5 mm
- double-row axial bearing in the swivel head
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	125 mm
Wheel width (S)	32 mm
Priemer príruby vidlice	60 mm
Bolt hole Ø	11 mm
Offset (F)	40 mm
Mounting height(H)	160 mm
Load	100 kg
Bearing type	Ihlové
Mounting type	Stredový otvor
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén
Typ brzdy	F

Application:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).