Data sheet
453 PUB-g150 p AS

Otočné rolovacie koliesko antistatické - spôsob upnutia: montážny otvor na skrutku.

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)		150 mm
Priemer príruby vidlice		76 mm
Bolt hole Ø		12.5 mm
Offset (F)		40 mm
Mounting height(H)		178 mm
Load		200 kg
Bearing type		guličkové
Mounting type		Stredový otvor
Attributes		
Farba behúňa		Sivá
Wheel centre colour		Black
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).