Data sheet
453F PUB-g100 p AS

Otočné rolovacie koliesko antistatické s brzdou - spôsob upnutia: montážny otvor na skrutku.

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)		100 mm
Priemer príruby vidlice		76 mm
Bolt hole Ø		12.5 mm
Offset (F)		40 mm
Mounting height(H)		124 mm
Load		200 kg
Bearing type		guličkové
Typ brzdy		F
Mounting type		Stredový otvor
Attributes		
Farba behúňa		Sivá
Wheel centre colour		Black
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).