# Data sheet
# 453 CPB-V100 AS

Otočné rolovacie koliesko antistatické - spôsob upnutia: montážny otvor na skrutku.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

| | | |
|---|---|---|
| **TREAD AND TYRE HARDNESS** | 70° Shore D | ●●●●● |
| **ROLLING RESISTANCE** | excellent | ●●●●● |
| **OPERATING NOISE** | satisfactory | ●●○○○ |
| **WEAR RESISTANCE** | good | ●●●○○ |
| **TEMPERATURE RANGE** | from -15 °C to +80 °C | ●●●○○ |

## Specifications

| | | |
|---|---|---|
| Diameter (D) | | 100 mm |
| Priemer príruby vidlice | | 76 mm |
| Bolt hole Ø | | 12.5 mm |
| Offset (F) | | 40 mm |
| Mounting height(H) | | 124 mm |
| Load | | 200 kg |
| Bearing type | | ihlové |
| Mounting type | | Stredový otvor |
| Attributes | | |
| Farba behúňa | | Čierna |
| Wheel centre colour | | Black |
| Wheel centre | | Polyamide |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).