Data sheet
473F CZC-K125

Swivel castor - mounting type: plug-in solid stem, with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +150 °C	

Specifications

Diameter (D)	125 mm
Priemer upínacieho drieku	22 mm
Dĺžka upínacieho drieku	45 mm
Offset (F)	40 mm
Mounting height(H)	151 mm
Load	200 kg
Bearing type	klzné
Typ brzdy	F
Mounting type	Hladký driek
Attributes	Non-marking
Farba behúňa	Prírodná krémová
Wheel centre colour	Prírodná krémová
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).