Data sheet
473F CNB-K100

Swivel castor - mounting type: plug-in solid stem, with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	60° Shore D	●●●●●
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)		100 mm
Priemer upínacieho drieku		22 mm
Dĺžka upínacieho drieku		45 mm
Offset (F)		40 mm
Mounting height(H)		124 mm
Load		100 kg
Bearing type		klzné
Typ brzdy		F
Mounting type		Hladký driek
Attributes		Non-marking
Farba behúňa		Prírodná biela
Wheel centre colour		Prírodná biela
Wheel centre		Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).