Data sheet

473F CPB-K080 AS H1

Otočné rolovacie koliesko antistatické s brzdou - spôsob upnutia: upínací driek (hladký čap) - zaisťovací otvor M6 (H1).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	●●●○○

Specifications

Diameter (D)	80 mm
Priemer upínacieho drieku	22 mm
Dĺžka upínacieho drieku	45 mm
Offset (F)	40 mm
Mounting height(H)	104 mm
Load	150 kg
Bearing type	klzné
Typ brzdy	F
Mounting type	Hladký driek
Attributes	
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).