Data sheet
473F CPB-V125 AS

Otočné rolovacie koliesko antistatické s brzdou - spôsob upnutia: upínací driek (hladký čap).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	●●●○○

Specifications

Diameter (D)		125 mm
Priemer upínacieho drieku		22 mm
Dĺžka upínacieho drieku		45 mm
Offset (F)		40 mm
Mounting height(H)		151 mm
Load		200 kg
Bearing type		ihlové
Typ brzdy		F
Mounting type		Hladký driek
Attributes		
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).