Data sheet
473 PUR-g075 p AS

Otočné rolovacie koliesko antistatické - spôsob upnutia: upínací driek (hladký čap).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)		75 mm
Priemer upínacieho drieku		22 mm
Dĺžka upínacieho drieku		45 mm
Offset (F)		40 mm
Mounting height(H)		97 mm
Load		130 kg
Bearing type		guličkové
Mounting type		Hladký driek
Attributes		
Farba behúňa		Sivá
Wheel centre colour		Black
Wheel centre		Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).