# Data sheet
# 473 PUR-g125 p AS

Otočné rolovacie koliesko antistatické - spôsob upnutia: upínací driek (hladký čap).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

| | | |
|---|---|---|
| **TREAD AND TYRE HARDNESS** | 98° ± 2° Shore A | ●●●●○ |
| **ROLLING RESISTANCE** | very good | ●●●●○ |
| **OPERATING NOISE** | good | ●●●○○ |
| **WEAR RESISTANCE** | very good | ●●●●○ |
| **TEMPERATURE RANGE** | od -30 °C do +70 °C | |

## Specifications

| | | |
|---|---|---|
| Diameter (D) |  | 125 mm |
| Priemer upínacieho drieku |  | 22 mm |
| Dĺžka upínacieho drieku | | 45 mm |
| Offset (F) |  | 40 mm |
| Mounting height(H) |  | 151 mm |
| Load |  | 160 kg |
| Bearing type |  | guličkové |
| Mounting type | | Hladký driek |
| Attributes | | |
| Farba behúňa | | Sivá |
| Wheel centre colour | | Black |
| Wheel centre | | Polyamide |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).