Data sheet

473F PUB-g100 p SS

Otočné rolovacie koliesko s brzdou - spôsob upnutia: upínací driek (hladký čap) - zaisťovací otvor M6 (H1).

VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	100 mm
Priemer upínacieho drieku	22 mm
Dĺžka upínacieho drieku	45 mm
Offset (F)	40 mm
Mounting height(H)	124 mm
Load	200 kg
Bearing type	ihlové
Typ brzdy	F
Mounting type	Hladký driek
Attributes	Non-marking
Farba behúňa	Hnedá
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).