Data sheet
423F ALU-G075-25 BR

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

Bracket 423 series:

Swivel castor with top plate (4 bolt holes)

- pressed steel, THK 3 ÷ 3,5 mm
- double ball bearing with calibrated races
- swivel head seal
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALU series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- non-marking
- yellow-brown color

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)	75 mm
Wheel width (S)	25 mm
Plate size (A x B)	105 x 85 mm
Bolt hole spacing (a x b)	80 x 60 mm
Bolt holes Ø	9 mm
Offset (F)	40 mm
Mounting height(H)	101 mm
Load	130 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking; Ochrana proti poraneniu nôh
Farba behúňa	Žlto-Hnedá
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).