Data sheet
724 PUC-G160 SS

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this castor uses vidlicu series 724 z steel plechu with pozinkovaním without Cr6, which ensures high durability against corrosion. Wheel centre z impact-resistant polyamidu so reinforced rebrom and tread z thermoplastic polyurethane elastomer are non-detachably mechanicky spojené, which increases trvanlivosť and elasticity for absorbciu záťaže. Thanks to dvom radiálnym ball ložiskám with krytmi offers smooth and maintenance-free chod, suitable for short aj dlhé transport vzdialenosti. An ideal choice for applications, where important gentleness k podlahám and reliability v demanding conditions.

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Wheel PUC SS series:

Wheel center:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- gray color

Tread:

- thermoplastic polyurethane elastomer
- chemically-bonded inseparable connection with the wheel cente
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- gray color

Application:

- manual handling equipment
- short transport distances (PUC-K)
- long transport distances(PUC-G)

TREAD AND TYRE HARDNESS	98° ± 2° Shore A
ROLLING RESISTANCE	very good
OPERATING NOISE	good
WEAR RESISTANCE	very good
TEMPERATURE RANGE	od -30 °C do +70 °C

Specifications

Diameter (D)	160 mm
Wheel width (S)	40 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	205 mm
Load	500 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).