Data sheet
724F ALE-G100

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors with brake uses vysoko odolné version with pozinkovanou vidlicou z steel plechu thickness 4-6 mm. Wheel centre z hliníkovej liatiny so reinforced uzatvoreným rebrovaním and antikoróznou ochranou is navulkanizovaný with plným elastickým rubber tread, which ensures veľmi dobrú priechodnosť cez nerovnosti and výborné tlmenie vibrácií. Thanks to dvom radiálnym ball ložiskám with krytmi achieves reliable and hladkú rotáciu. Mechanizmus brake F locks rotation wheel and vidlice v direction aktuálneho natočenia, thereby increases safety and stability. Nosný diel bearing is kovaný and vytvrdzovaný, which guarantees a long service life. Suitable for tvrdé floor (pancierové) aj nerovné surfaces, where combines durability with tichým chodom.

Bracket 724 series:

Swivel castor with top plate (4 bolt holes)

- heavy-duty version
- pressed steel, THK 4 ÷ 6 mm
- shaped and hardened bearing
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALE series:

Wheel center:

- aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- elastic solid rubber
- chemically-bonded inseparable connection with the wheel center (vulkanized)
- excellent at crossing obstacles
- vibration-absorbing
- silent operation
- black color

TREAD AND TYRE HARDNESS	65° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	good	●●●○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -30 °C do +80 °C	

Specifications

Diameter (D)		100 mm
Wheel width (S)		50 mm
Plate size (A x B)		135 × 110 mm
Bolt hole spacing (a x b)		105 × 80/75 mm
Bolt holes Ø		11 mm
Offset (F)		60 mm
Mounting height(H)		145 mm
Load		100 kg
Bearing type		Ball
Mounting type		Mounting bracket
Tread material		Guma a TPE
Attributes		Nízka hlučnosť
Farba behúňa		Čierna
Wheel centre colour		Hliníková
Wheel centre		Hliníková liatina
Typ brzdy		F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).