Data sheet
532 NOB-V075

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model 532 NOB predstavuje fixed rolovacie castor with mounting doskou na four otvory, where zinc-plated steel vidlica ensures durability. Wheel centre z polypropylene is durable to prasknutiu and svetlo-sivej farby, while tread z thermoplastic rubber elastomer v tmavo-sivej farbe is non-detachably mechanicky combined with wheel centre, which ensures long service life and quiet non-marking operation. The design includes ihlové bearing, where vonkajší krúžok tvorí material wheel centre, with ihlíčkami z steel tvrdosti 25 HRC and klietkou z polyamidu PA6, suitable na short transport distances. Thanks to the use of of this bearing achieves spoľahlivá operation with low údržbou. An ideal choice for sklady, malé výroby and operation, where potrebná ľahká manipulácia and gentleness k podlahám.

Bracket 532 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - roller:

- the outer ring of the bearing formed by the wheel center material

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	75 mm
Wheel width (S)	30 mm
Plate size (A x B)	105 x 85 mm
Bolt hole spacing (a x b)	80 x 60 mm
Bolt holes Ø	9 mm
Mounting height(H)	100 mm
Load	100 kg
Bearing type	Ihlové
Mounting type	Mounting bracket
Tread material	Guma a TPE
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).