Data sheet
522F XC-V100 BR

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this castor z radu XC uses durable wheel centre v spojení with rubber tread, which guarantees gentleness k podlahovým povrchom and tichú operation. Thanks to kľznému bearing ensures maintenance-free operation with dlhou service lifeou, while the integrovaná brake offers bezpečné zafixovanie pozície. An ideal choice for applications v industrial and komerčných priestoroch, where important reliability and jednoduchá montáž.

TREAD AND TYRE HARDNESS	90° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	sufficient	●○○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

Diameter (D)	100 mm
Wheel width (S)	30 mm
Plate size (A x B)	105 x 85 mm
Bolt hole spacing (a x b)	80 x 60 mm
Bolt holes Ø	9 mm
Offset (F)	35 mm
Mounting height(H)	128 mm
Load	80 kg
Bearing type	Ihlové
Mounting type	Mounting bracket
Tread material	Guma a TPE
Farba behúňa	Čierna
Wheel centre colour	Black
Wheel centre	Oceľ
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).