Data sheet
623AN3 CPC-K125

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this castor uses thermoplastic elastomér v behúni, which ensures tichú and hladkú operation, ideálne for kancelárske alebo domáce prostredia. Thanks to the use of klzného bearing offers maintenance-free operation and long service life, while the zinc-plated vidlica increases durability against corrosion. An ideal choice for applications vyžadujúce easy manipuláciu and reliable montáž na four otvory, thereby zlepšuje stability and safety during use.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).