Data sheet
623TAN3 CPC-K125

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this castor includes montážnu dosku na four otvory (príruba) for simple and bezpečnú installation, which increases stability during operation. Use odolných materiálov, such as is thermoplastic elastomér for tread and zinc-plated vidlica, ensures long service life and resistance to wear. Thanks to kĺznému bearing castor ensures quiet and plynulý chod, while brzdový mechanizmus allows precise zastavenie and fixation nákladu. An ideal choice for industrial applications, where potrebná reliability and gentleness k podlahám.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).