Data sheet
623AN3 CPC-K160

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this rolovacieho castors uses montážnu dosku na four otvory (príruba) for simple and bezpečnú installation. Thanks to the use of high-quality tread z thermoplastic elastomer and durable wheel centre achieves excellent durability against wear. Klzné bearing ensures maintenance-free operation with minimálnym trením, thereby predlžuje service life komponentov. An ideal choice for applications vyžadujúce plynulý and quiet movement v industrial alebo komerčných priestoroch, where important gentleness k podlahám and reliability v dlhodobej operation.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).