Data sheet
623TAN3 CPC-K160

Swivel castor - mounting type: top plate (4 bolt holes).



The design of this rolovacieho castors uses montážnu dosku na four otvory (príruba) for bezpečné and fixed mounting. Tread z thermoplastic elastomer guarantees quiet and non-marking operation, while the kvalitné bearing ensures plynulú rotáciu and long service life. Thanks to the use of pozinkovanej vidlice and durable wheel centre is castor suitable for demanding industrial prostredia. An ideal choice for applications vyžadujúce precise control movement and reliable brzdu.

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).