Data sheet
624F ALUO-G200

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this castor includes hliníkový wheel centre so reinforced rebrovaním, which is antikorózny and durable, combined with liateho polyurethane elastomer behúňom, which nepoškodzuje floor and is characterised by dobrou elasticitou. Thanks to dvom radiálnym ball ložiskám with krytmi and zinkovanej vidlici without Cr6 offers nízky valivý odpor and long service life. Mechanizmus brake F allows zablokovanie rotation v current direction, which increases safety. An ideal choice for stredne demanding applications na tvrdých aj mäkkých industrial floors with nerovnosťami, suitable for nepretržitú operation.

Bracket 624 series:

Swivel castor with top plate (4 bolt holes)

- medium-duty version
- pressed steel, THK 4 ÷ 5 mm
- double ball bearing with calibrated races
- swivel head seal
- zinc-plated, Cr6-free

Discription of the brake F:

- the brake system prevents the rotation of the wheel and bracket in the direction of the current rotation

Wheel ALUO series:

Wheel center:

- die-cast aluminium
- reinforced with closed ribbing
- corrosion-free
- aluminium color

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- High-profile rounded shape
- good elasticity, good at preserving floor surfaces
- non-marking
- low level of starting and rolling resistance
- cream color RAL 9001

TREAD AND TYRE HARDNESS	87° ± 5° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	240 mm
Load	600 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Krémová
Wheel centre colour	Hliníková
Wheel centre	Hliníková liatina
Typ brzdy	F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).