Data sheet
673 XB-G160

Swivel castor - mounting type: plug-in solid stem.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors includes zinc-plated vidlicu z steel plechu with hrúbkou 3 až 3,5 mm, which provides robustnú podporu. Wheel centre is made z steel plechu and zinkovaný without Cr6, which increases durability against corrosion. Tread z prémiovej plnej rubber ensures high comfort jazdy, gentleness k jazdnému surface and quiet operation. Use dvoch radiálnych guličkových ložísk with krytmi allows plynulú rotáciu and long service life with minimálnou údržbou. An ideal choice for lightweight manipulačné equipment v skladoch, small výrobách and prevádzkach, where important reliability and ochrana floor.

Bracket 673 series:
Swivel castor with plug-in solid stem

- standard version
- steel THK 3 ÷ 3,5 mm
- double ball bearing with calibrated races
- zinc-plated, Cr6-free

Wheel XB series:
Rim:

- pressed steel
- zinc-plated, Cr6-free

Tyre:

- premium solid rubber
- high operational comfort
- good floor preservation properties
- low-noise operation
- black color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	80° ± 5° Shore A	●●●○○
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

Diameter (D)		160 mm
Wheel width (S)		45 mm
Priemer príruby vidlice		102 mm
Priemer upínacieho drieku		27 mm
Dĺžka upínacieho drieku		65 mm
Offset (F)		56 mm
Mounting height(H)		195 mm
Load		205 kg
Bearing type		Ball
Mounting type		Hladký driek
Tread material		Guma a TPE
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).