Data sheet
633P CPC-G200

Fixed castor - mounting type: top plate (4 bolt holes), with brake.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this pevného rolovacieho castors series 633P combines zinc-plated vidlicu z steel plechu with mounting doskou na four otvory, which allows simple and bezpečnú installation. Vstrekovaný polyamidový tread ensures excellent resistance to corrosion, alkoholom, soliam, tukom and zriedeným kyselinám či zásadám. Dvojpáková brake typu P mechanicky locks rotation wheel, ponúkajúc jednoduché ovládanie ON/OFF. Dve radiálne ball bearings ensure plynulý chod and long service life during trvalých záťažiach. An ideal choice for straight polyurethane floor, equipment with trvalou záťažou and prepravu na short aj dlhšie vzdialenosti, where important chemická durability and spoľahlivá brake.

Bracket 633 series:

Fixed castor with top plate (4 bolt holes)

- pressed steel
- zinc-plated, Cr6-free

Discription of the brake P:

- the brake system prevents the rotation of the wheel double-lever ON/OFF version

Wheel CPC series:
Injection polyamide:

- corrosion-free
- high chemical resistance to alcohol, salts, fats, some acids and bases in dilute concenrations (see spreadsheet chemical resistance of materials)
- natural white color

Application:

- even polyurethane floors
- equipment with a permanent load
- short distances (CPB-K)
- long distances (CPB-g)

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	70° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	from -15 °C to +80 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	240 mm
Load	350 kg
Bearing type	Ball
Typ aretácie	-
Mounting type	Mounting bracket
Tread material	Plastic
Attributes	Non-marking
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide
Typ brzdy	P

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).