Data sheet
624 PUO-G150

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this swivel rolovacieho castors uses stredne odolnú vidlicu z pozinkovanej steel with axial bearing and tesnením otoča for smooth movement. Wheel centre z impact-resistant polyamidu so reinforced rebrom and antikoróznou finish non-detachably combined with behúňom z thermoplastic polyurethane elastomer provides excellent elasticity and schopnosť absorbovať high load. Thanks to dvom radiálnym ball ložiskám with krytmi ensures reliable and maintenance-free operation. An ideal choice for ručné transport equipment v environments, where important ochrana floors and quiet operation.

Bracket 624 series:

Swivel castor with top plate (4 bolt holes)

- medium-duty version
- pressed steel, THK 4 ÷ 5 mm
- double ball bearing with calibrated races
- swivel head seal
- zinc-plated, Cr6-free

Wheel PUO series:

Wheel center:

- impact-resistant structural polyamide
- reinforced bearing rib
- corrosion-resistant
- black color

Tread:

- thermoplastic polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and absorption of high load capacity
- notch toughness
- very good floor preservation
- non-marking
- cream color

Application:

- manual handling equipment

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	150 mm
Wheel width (S)	45 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Offset (F)	56 mm
Mounting height(H)	195 mm
Load	500 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Krémová
Wheel centre colour	Black
Wheel centre	Polyamide

Bearing - ball:

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).