Data sheet
653F NMB-K160



The design of this wheel uses polypropylénový wheel centre combined with termoplastickým elastomérovým behúňom, which guarantees low hlučnosť and protection floor surfaces. Klzné bearing ensures non-marking operation and long service life without the need for maintenance, while the zinc-plated vidlica increases resistance to corrosion. An ideal choice for industrial and komerčné prostredia, where important reliability and quiet operation, napríklad v skladoch, nemocniciach alebo kanceláriách.

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).