Data sheet
634 PUC-G200 AS

Fixed castor - mounting type: top plate (4 bolt holes).



VYROBENÉ NA SLOVENSKU
MADE IN SLOVAKIA

ESD

The design of this pevného rolovacieho castors uses robustný wheel centre and rubber tread z thermoplastic elastomer, which ensures high durability and tichú operation. Thanks to kľznému bearing offers maintenance-free operation and long service life, while the mounting doska na four otvory allows simple and bezpečnú installation. An ideal choice for industrial and komerčné prostredia, where important reliability and gentleness k podlahám, with možnosťou použitia v skladoch, workshops alebo logistics centrách.

TREAD AND TYRE HARDNESS	98° ± 2° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	very good	●●●●○
TEMPERATURE RANGE	od -30 °C do +70 °C	

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Plate size (A x B)	135 x 110 mm
Bolt hole spacing (a x b)	105 x 80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	240 mm
Load	600 kg
Bearing type	Ball
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Black
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).